



SANJAY POWER CONTROLS

PRODUCT CATALOGUE 2026

AGRICULTURAL & INDUSTRIAL POWER SOLUTIONS

Powering Progress • Protecting Motors • Supporting Agriculture



Manufacturing | Sales | Service

☎ 9845249160 | 9144388956

📍 Belagavi, Karnataka

Trusted Quality • Timely Service • Customer Satisfaction



AUTOMATION & MOTOR CONTROL SOLUTIONS

Auto Start Unit

HSN Code - 85369020

(Model-C)

- System Voltage 415V
AC $\pm$ 30% 50Hz
- On Delay Time 30 Sec.
- Industrial Grade Plastic Body



Water Level Controller with Flot Switch

HSN Code - 85369020

(Model WLC002)

- System Voltage 230V
AC $\pm$ 30% 50Hz
- Using for Double Sensor
Upper & Lower Tank
- Auto Manual Function



Auto Start with Preventor (Model Pv32)

HSN Code - 85369020

- System Voltage 415V
AC $\pm$ 30% 50Hz
- On Delay Time 30 Sec.
- On Time 5 Sec.
- SSP (Single Phasing Protection)
- Led Indication
- Observe Sequence OK Light Glowing
- Industrial Grade Plastic Body



Water Level Controller with Flot Switch

HSN Code - 85369020

(Model WLC05)

- System Voltage 230V
AC $\pm$ 30% 50Hz
- Using for Upper Tank
with Overload & Dryrun Protection
- Auto Push Button Setting
- Separate Indicators for Overload
Tank Full & Tank Empty Auto
Manual Facility



Mini Auto Start with Preventor + Timer

HSN Code - 85369020

(Model 156)

- System Voltage 415V
AC $\pm$ 30% 50Hz
- On Delay Time Adjustable
1 to 5 minutes
- SSP (Single Phasing Protection)
- Led Indication
- Observe Sequence OK Light Glowing
- Industrial Grade Plastic Body



Digital Voltage & Amper Meter

(Model
Digi / Timer 001)

- System Voltage
230 V To 415 V
- Support Ampere
1 to 80 A



RTC Digital Timer

(Model
RTC Timer 003)

- Input Voltage 230 V /
50Hz AC
- Timing Capacity -
4 Slots Per Day
- Digital Type
- Display Type - 7 Segment Display
- Usage / Application Industrial



2/3 & JUICE Change Over

HSN Code - 85369020

(Model SPC 05)

- System Voltage
300 - 415V
3Phase 50Hz
- HP 1 to 15
- For Agriculture
Submersible Pumpset



Mobile Controller Starter (GSM)

HSN Code - 85369020

- Call & SMS Function
- Useful for 1 to 50 HP
3 Phase Motor
- Overload & Dryrun
Protection Function
- Single Phase Preventer (SPP)
- Cooling Motor Protection
- On Display RYB Voltage & RYB Current



(Model)